# EV9628-29 Quad-XC<sup>2</sup> Cartridge Kit Replacement cartridge kit for Everpure High Flow CSR Plus-XC<sup>2</sup> **Systems** BENEFITS Convenient replacement cartridge kit contains all necessary cartridges to service filters in specific High Flow CSR Plus combination systems. XC Kit includes (1) EC210 prefilter, (4) XC<sup>2</sup> filter cartridges, and (1) SS-IMF with spacer XC<sup>2</sup> Reduces chlorine taste and odor and other offensive contaminants that can adversely affect the taste of beverages New and improved Micro-Pure II media with AgION<sup>TM</sup> antimicrobial protection inhibits any potential bacterial growth Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size and reduces possible health contaminants such as asbestos fibers and Cryptosporidium and Giardia Quad-XC<sup>2</sup> Replacement Cartridge Kit: cysts EV9628-29 20" prefilter cartridge captures larger dirt particles and extends the life of the ${\rm XC}^2$ cartridges SS-IMF cartridge inhibits limescale buildup in ice machines and coffee brewers.

#### XC<sup>2</sup> cartridges are NSF Certified under NSF/

### INSTALLATION TIPS

## OPERATION TIPS

Install vertically with cartridges hanging down Change cartridges on a regular 6 m preventative maintenance program

Allow 2-1/2" clearance below the cartridge for easy cartridge replacement

Flush cartridges by running water through system for five minutes at full flow

Install SS-IMF cartridge in SR-X bowl vertically with black o-band seal up

Change cartridges on a regular 6 month

Change cartridges when capacity is reached or when pressure falls below 10 psi

Change SS-10 cartridge before Hydroblend™ compound is completely used up

Replace EC210 cartridge when dirt has penetrated through to the inner core of the cartridge

Always flush the filter cartridges at time of installation and cartridge change

## A P P L I C A T I O N / S I Z I N G

Flow CSR Plus Combination Systems

For foodservice applications

Use when extreme water conditions require longer life and larger capacity carbon filter

33% more capacity than the MC<sup>2</sup> filter cartridge

# S P E C I F I C A T I O N S

**Overall Dimensions:** 

XC<sup>2</sup> = 29.69"H x 34"W x 6.75"D ; EC210 = 20"H x 3.38" Diameter ; SS-IMF = 6-7/8"H x 1-5/16" Diameter

The SS-IMF Spacer (EV3114-69) may be used to extend the height of the SS-IMF cartridge by approximately 1-3/4" for a better fit into longer bowls.

Service Flow Rate: Maximum 6.7 gpm (25.4 Lpm)

Pressure Requirements: 10 psi -125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35°F - 100°F (2-38°C)

The contaminants or other substances removed or reduced by this drinking water system are not necesssarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.

Quad-XC<sup>2</sup> Cartridge Kit



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction Mechanical Filtration Unit Particulate Reduction, Class I: 99.9+% reduction of particles one-half micron and larger in size Standard No. 53: Health Effects Mechanical Filtration Unit Turbidity Reduction Cyst Reduction Asbestos Reduction



EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe: N.V. EVERPURE (EUROPE) S.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals Belgium Tel 32 -14-283500 Fax 32-14-283505 In Japan: EVERPURE JAPAN LLC Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 Japan Tel 81-(0)42-775-3011 Fax 81-(0)42-775-3015

Everpure, LLC 1040 Muirfield Drive Hanover Park, IL 60133 Ph: 630-307-3000 Fax: 630-307-3030