

Watts® ROs with Kwik-Change™ Cartridges

Simply the “best” of the “best”!

Internal valve shuts-off flow during cartridge and membrane replacement.

Hinged bracket for easy cartridge removal and replacement make change outs so easy, anyone can do it!

Best Seller. Try It Today!

Proprietary filter cartridges and membranes are installed and removed by a simple 1/4 turn.

Cartridges have double o-rings to prevent leaks!



WQA Gold Seal
Certified to
NSF / ANSI
Std. 58




Watts® Kwik-Change™ Systems are designed for consumers that demand the “best”. Unlike conventional reverse osmosis systems, Watts drinking water systems with Kwik-Change cartridges have no sumps, so their proprietary filter elements and membranes are easy to replace.

Full Product Line Available, Including:

50 GPD Models • 100 GPD Models • Metal Tanks
Plastic Tanks • Top Mount Faucets • Standard Faucets
Models For Coolers • Custom Systems
Drinking Water Systems With Filter Elements
& Hollow Fiber Membranes.

Features & Benefits

- Cartridges are connected and removed with a simple 1/4 turn.
- No filter sumps! No fuss! No mess!
- Automatic shut-off when cartridges are removed.
- Tank and faucet options available.
- Valves are built into the heads to prevent back-flow for water quality assurance.
- WQA Gold Seal Certified to NSF/ANSI Std. 58.



Watts® Top Mount Faucets are mounted from above the counter top.



Long Reach Chrome Faucet



Metal Storage Tank



RO Pro® Storage Tanks
Only 9” wide, takes less space and won’t chip, rust or dent!

Watts® Kwik-Change RO systems are so easy to service you'll get great quality water every time!



Kwik-Change RO with Permeate Pump.

Conventional RO Systems

VS.

Kwik-Change RO System

Conventional RO systems may provide high quality water. However, cartridges and membranes are difficult to replace because they are installed in housings and must be removed. This procedure includes the need to shut off and drain down the system, open the housings with a wrench, remove cartridges, empty water from the sumps, clean the filter and membrane housings, replace cartridges, re-pressurize, and check for leaks.

Because conventional systems are difficult to service, routine maintenance may be delayed. Therefore, consumers may not get the quality water they desire, unless a qualified dealer is called to service their system.

No Sumps! No Mess! No Fuss!

- Hinge bracket for easy handling.
- Automatic shut off when cartridges are removed with a simple, 1/4 turn.
- No need to disconnect tubing when replacing membranes.
- Integrated check valves between cartridges and membrane prevent back-flow.
- Cartridges have double o-rings so they will not leak.
- Quick connect fittings for easy installation.

Models

Model Number	Pump	Stage	Capacity (GPM)	Size Elements	Faucet	Tank
WQC4RO11-50PT	No	4	50	11"	Top mount	RO-PRO®
WQC4RO11-50MT	No	4	50	11"	Top mount	Metal
WQC4RO11-50MTLR	No	4	50	11"	Long reach	Metal
WQC4RO13-100PT	No	4	100	13"	Top mount	RO-PRO®
WQC4RO13-100MT	No	4	100	13"	Top mount	Metal

Permeate Pump Models

Model Number	Pump	Stage	Capacity (GPM)	Size Elements	Faucet	Tank
WQC4RO11-50PTPP	Yes	4	50	11"	No faucet	RO-PRO®
WQC4RO11-50MTTPP	Yes	4	50	11"	No faucet	Metal
WQC4RO13-100PTPP	Yes	4	100	13"	No faucet	RO-PRO®
WQC4RO13-100MTTPP	Yes	4	100	13"	No faucet	Metal

Note: All models listed above use 3/8" tubing from unit to tank to faucet.

Replacement Elements

Model	Element	Sediment	Carbon	Membrane	GAC
50 GPD System	11"	WQCSC11	WQCCC11	WQCM11-50	WQCGAC11
100 GPD System	13"	WQCSC13	WQCCC13	WQCM13-100	WQCGAC13